
Conversion of Sugar Mixtures into Products using Substrate Selective Uptake

March 7, 2008


Mark A. Eiteman, Elliot Altman
CMBE
University of Georgia
eiteman@engr.uga.edu

Biorefinery Concept




Source: www.eere.energy.gov/biomass

Sugar Platform




Approach #1




Ethanol

Approach #2



Process Concept



Materials and Methods

Strains (E. coli)

ZSC113 (ptsG manZ glk) ALS1008 (xylA) ALS1060 (ptsG manZ glk xylA)

Batch

16 g/L glucose, 8 g/L xylose, 10 g/L acetate

Fed-Batch


Exponential, Varied Concentrations

Conditions

 $1.0L, 37^{\circ}C, pH = 7.0$


Xylose Consumption

ZSC113




Glucose Consumption

ALS1008




Xylose and Glucose Consumption

ZSC113 and ALS1008




Xylose and Glucose Consumption

ZSC113 and ALS1008



Acetate Consumption

ALS1060




Advantages of Approach

- Cellular nutrients from acetate-selective cells in Stage 1 are available to support growth of cells present in Stage 2.
- Metabolic engineering strategies can focus on improving the individual production strains independently. We do not need to compromise one objective for another.
- The system adapts to fluctuations in the feed stream; that is, cultures actually grow in concert with the feed composition.

Long Term Objectives

Lignocellulosic biomass is a complex mixture which requires special high-temperature/high-pressure processes to generate monomers.

The resulting hydrolysate is complex, and requires multiple strains with specialized abilities to work in concert to convert monomers into ethanol or other bio-based products.



Acknowledgments

Synergy Parametrics, LLC and







